

The logo for GigaSpire BLAST u6xw, featuring a white Wi-Fi symbol above the text 'GigaSpire' in white and orange, with 'BLAST u6xw' in white below it.

GigaSpire[®] BLAST u6xw



The Calix GigaSpire[®] u6xw (GS4227W) is a new generation smart home system that integrates optical network termination (ONT) and residential gateway functionality into a single system*. It supports virtually any passive optical network (PON) and Ethernet technology, while providing the ultimate Wi-Fi experience. Besides supporting broadband connectivity of data and video services, this intelligent, high-performance system offers the latest 802.11ax 'Wi-Fi 6' technology. The GigaSpire BLAST u6xw provides switching and routing functions that support multi-Gigabit throughput for IPTV video and data services.

MULTI-GIGABIT SUBSCRIBER EXPERIENCE

The GigaSpire BLAST u6xw is a premium smart home integrated system that delivers the latest Wi-Fi 6 certified technology (802.11ax). The GigaSpire BLAST u6xw uses an SFP+ cage supporting a 10 Gigabit link* at the subscriber's premises to provide carrier-class WAN, including GPON and XGS PON, as well as 1 and 10 Gigabit Ethernet (both copper and Active Ethernet) options. On the LAN side, Wi-Fi and four (4) Gigabit Ethernet interfaces are available for customer multi-media devices.

The GigaSpire BLAST u6xw enables residential subscribers to receive Gigabit broadband data, Internet Protocol (IP) video, and voice (POTS) services. Using the latest 802.11ax technology in both the 2.4 and 5 GHz radios, the GigaSpire BLAST u6xw incorporates 6x6 streams of Wi-Fi delivery (2x2 @ 2.4 GHz and 4x4 @ 5 GHz). In addition, with multi-user multiple-input and multiple-output (MU-MIMO) and beamforming, the GigaSpire BLAST u6xw allows service providers to extend the access network inside the home and establish a strategic location for the delivery and control of broadband services. With Wi-Fi being the de facto wireless data communication technology of choice for consumers, Calix engineered the GigaSpire BLAST u6xw for optimal whole-home coverage with simultaneous dual-band 2.4 GHz and 5 GHz operation and dynamic beamforming in both spectrums.

Leveraging the latest Wi-Fi 6 features, the GigaSpire BLAST u6xw provides longer range, higher efficiency, and less interference compared to earlier generations of Wi-Fi technology. The GigaSpire BLAST u6xw also supports the entire 5 GHz band, including Dynamic Frequency Selection (DFS) channels and can be provisioned to support 160 MHz channel bandwidth at 5 GHz. The GigaSpire BLAST u6xw easily delivers HD and UHD (ultra-HD) video and data throughout a subscriber's

home in an increasingly video-rich and mobile broadband environment. Ensuring consumers can have ultra-fast Wi-Fi throughout their premises, the GigaSpire BLAST u6xw provides the latest generation of redundant Wi-Fi 6 mesh via the Calix GigaSpire Mesh GigaSpire BLAST u4m (please see the GM1028 data sheet for more information). With the GigaSpire BLAST u6xw as the hub, and the Mesh GigaSpire BLAST u4m as the satellite extenders, consumers can truly gain the whole home/smart home experience. For even higher mesh performance, an additional GigaSpire BLAST u6 system, such as the GigaSpire BLAST u6.1, can also be deployed as a mesh unit. This means that two GigaSpire BLAST u6 systems can connect to each other with one being the residential gateway and the other being the mesh.

EASY TO INSTALL, ACTIVATE, AND MAINTAIN

With the GigaSpire BLAST u6xw integrated system, Calix has redefined how to install and activate residential services at a subscriber's premises. Using CommandIQ® and a phone or laptop, a field technician can install and apply the subscriber's service profile without special equipment or assistance from the central office. Calix also provides the innovative Calix Support Cloud (CSC), which allows the service provider to configure, activate and upgrade the GigaSpire BLAST u6xw quickly from a remote location using in-band management, TR-069, or ONT Management Control Interface (OMCI).

Extensive troubleshooting capabilities, remote software downloads, and easy-to-use service activation features ensure that services are delivered and maintained without needless truck rolls and hardware upgrades. Deploying GigaSpire BLAST u6xw systems allows service providers to reduce their operational expenses while

Note: XGS PON technology, although referred to as "10 Gig PON" is limited to a maximum symmetrical throughput of approximately 8.5 Gbps, owing to various overhead limitations and network conditions.

effectively delivering the Gigabit experience to their subscribers. If a PON module is being used, PON configuration and management is done via the OMCI protocol.

CALIX EXPERIENCE INNOVATION PLATFORM

All GigaSpire BLAST systems are powered by the Calix Innovation Experience Platform.

This container-based platform allows service providers to quickly change and adapt their services to embrace new technologies and offer new, value-added services. This approach can generate recurring revenue and increase subscriber satisfaction.

KEY ATTRIBUTES

Home Gateway:

- Layer 2 bridge and Layer 3 routing for High Speed Internet (HSI) data and IPTV video services
- DHCP server options
- DHCP (IPoE) and PPPoE network connections
- Network Access Translation (NAT), public to private IP addressing
- Configurable IP address schemes, subnets, static-IP addresses
- DNS server
- Bridge port assignment and data traffic mappings
- Port forwarding
- Firewall and security
- Application and website filtering
- Selectable forwarding and blocking policies
- DMZ hosting
- Parental controls, time of day usage
- Denial of service (DoS) protection
- MAC filtering
- Time/Zone support
- Universal Plug-and-Play (UPnP)

Wi-Fi:

- 2.4 GHz and 5 GHz, simultaneous dual-band
- 5 GHz 802.11ax (Wi-Fi 6) certified, 802.11a/n/ac compatible
- 6x6 streams (2x2 @ 2.4 GHz and 4x4 @ 5 GHz)
- 2.4 GHz 802.11ax (Wi-Fi 6) certified, 802.11b/g/ac compatible

- WPA/WPA2/WPA3; WEP 64/128 bit encryption
- PuF (Physical Unclonable Functions)
- WPS push-button
- 4x4 DL/UL MU-MIMO with beamforming
- 1024 QAM; OFDMA; BSS Coloring
- DCM (Dual Carrier Modulation)
- TWT (Target Wake Time) for IoT clients

Wi-Fi Redundant Mesh:

- Self Managed: self configuration, Air time fairness
- Dynamic Mesh: load balancing, band/node steering; interference management
- Self Healing: backhaul failover; diagnostics; events

SFP+ interface:

- Full 10 Gigabit bandwidth
- Supporting several SFP WAN modules, including: GPON, 1 Gigabit Ethernet (copper) and 10 Gigabit Ethernet (copper), XGS (future release), 1G and 10G Active Ethernet (future release)

Gigabit Ethernet (GE)

LAN interfaces:

- Four (4) ports of multi-rate 10/100/1000 BASE-T Ethernet, auto-negotiating for residential IPTV and data services

Two voice lines:

- Carrier grade SIP, H.248 (aka Megaco) and MGCP¹

USB port:

- USB 2.0 - Type A host interface

Supports multiple data service profiles

Traffic management and Quality of Service (QoS):

- 802.1Q VLANs
- 802.1p service prioritization
- Q-in-Q tagging
- Multiple VLANs
- DiffServ
- Pre-defined QoS on service type
- MAP-T

IPTV, IGMPv2, future support of IGMPv3:

- IGMP Snooping and Proxy
- IGMP Fast Leaves

Gateway Management:

- CSC (Calix Support Cloud)
- TR-069
- Local Home Gateway GUI, access provisionable
- Remote WAN side GUI access
- Default username/password

AC to 12 V DV power adapter

Optional UPS power unit available

¹ Currently supporting MetaSwitch and Ribbon softswitches

SPECIFICATIONS

Dimensions

- Width: 5.13 in (13 cm)
- Height: 10.13 in (25.73 cm)
- Depth: 5.13 in (13 cm)
- Weight: 42 oz (1.19 kg)

WAN Interface

- Interface: SFP+ cage (with options for GPON, 1 GBT, 10 GBT, XGS, and both 1G and 10G Active Ethernet)

Interfaces

- Wireless: 2.4 GHz 2x2 and 5 GHz 4x4 internal antennas
- LAN Data/IPTV: Four (4) 10/100/1000 BASE-T Ethernet port, RJ 45 connectors
- WAN: SFP+ cage
- USB: USB 2.0 Type A
- Voice: Two ports supporting Metaswitch; C15; C20 SIP; H.248 and MGCP
- Power: Single pin and 8-pin

Data

- Drop length: 328 feet (100 m) max using CAT5 cable for GigE
- Auto MDI/MDIX crossover for 1000BASE-TX, 100BASE-TX
- 10GBT: 110 feet (30m) CAT6e/7 cable
- Traffic Management and QoS: 802.11Q VLAN; 802.11p voice, video, data and management priorities; Q-in-Q tagging

Wireless

- 2.4 GHz 802.11 b/g/n/ac/ax
- 2x2 UL/DL MU-MIMO
- 5 GHz 802.11 a/n/ac/ax
- 4x4 DL/UL MU-MIMO, implicit/explicit high-power, dynamic beamforming (5 GHz radio)
- 2x2 DL/UL MU-MIMO explicit high-power, dynamic beamforming (2.4 GHz radio)
- 2.4 GHz and 5 GHz simultaneous
- DCM, TWT, extended GI
- Auto channel selecting and interference detection
- WPS, WPS push button
- Wi-Fi multimedia (WMM)

Remote Management

- TR-069 remote management
- TR-098 Internet Gateway Device Data Model

Environmental

- Operating temperature: Indoor ambient temperature, 0° to 40°C (32° to 104° F)
- Operating and storage relative humidity: 10 to 90 % and 5 to 95% non-condensing respectively

Certification and Compliance

- Emissions: FCC Part 15 Class B IC ICES-003 Class B CISPR-22
- Safety: UL 62368 and UL 1697 approved
- IEEE: 802.3, 802.3AB, 802.3U, 802.11p, 802.11Q
- Wi-Fi Alliance Certified 802.11ax



- USB-IF Compliance USB 2.0



Powering and Alarms

- Single pin and 8-pin
- Input voltage: 12 V DC (nominal)
- External Power Adapter: 12 V DC, 3A
- Optional UPS power unit available

Ookla-based Performance Testing

- Subscribers can run an Ookla-based performance test from within the Calix CommandIQ® mobile app
- Symmetrical speed test results in excess of 3 Gbps are possible with the GigaSpire BLAST u6xw system when using a 10 GigE (copper), 10 GigE (Active Ethernet) or XGS SFP module.

ORDERING INFORMATION

Calix GS4227W GigaSpire BLAST u6xw

100-05613..... GS4227W GigaSpire BLAST u6xw, SFP+, 4 GE LAN, 2 POTS,
Dual Wi-Fi – AM Power Adapter

Calix GS4227W GigaSpire BLAST u6xw Bundles

000-01205..... GS4227W GigaSpire BLAST u6xw, SFP+, 4 GE LAN, 2 POTS, Dual Wi-Fi – AM Power
Adapter (with GPON SFP module)

000-01204..... GS4227W GigaSpire BLAST u6xw, SFP+, 4 GE LAN, 2 POTS, Dual Wi-Fi – AM Power
Adapter (with XGS SFP module; future release)

000-01210..... GS4227W GigaSpire BLAST u6xw, SFP+, 4 GE LAN, 2 POTS, Dual Wi-Fi – AM Power
Adapter (with GE Active Ethernet SFP module; future release)

Calix GS4227W GigaSpire BLAST u6x/u6xw SFP Modules

100-05609..... GPON ONT SFP module

100-05656..... 1GE SFP, UTP Copper, RJ-45, 100m, I-Temp

100-05622..... 10GE SFP+, UTP Copper, RJ-45, 100m, I-Temp

100-05610..... XGS ONT SFP+ module (future release)

100-05620..... 1 Gigabit Active Ethernet SFP module (future release)

100-05721..... 10GE BIDI SFP+, Single Mode single fiber Upstream transceiver, 20Km, 1330nm,
SC/APC, I-Temp (future release)

Calix GS4227W GigaSpire BLAST u6xw Power Adapter

100-05793..... GigaSpire BLAST u6xw (GS4227W) Power Adapter, 12 V, 3 A – AM Type A

Optional Mounting Bracket

100-05751..... GS4227W Mounting Bracket — Quantity 14

Optional Uninterruptible Power Supply (UPS)

100-04068..... Indoor UPS (8 hour support), Wall Mount or Desktop, 12 V, 7.2 AH, 36 W, Black – AM,
Type B, Grounded

100-05345..... Indoor UPS (24 hour support), Wall Mount or Desktop, 12 V, 20 AH, 75 W, Audible Alarm,
Regulated Output R3 Production

ORDERING INFORMATION

UPS Power Adapters

100-03893..... Indoor UPS Power cord, 7-pin UPS to 8-pin ONT Male, 1m, black

100-03894..... Indoor UPS Power cord, 7-pin UPS to 8-pin ONT Male, 3m, black

100-03895..... Indoor UPS Power cord, Unterminated to 8-pin ONT Male, 6m, black

Removeable Branding Plate

100-05763..... Blank, removable branding plate. Contact your sales representative to order branding plates that can be customized with your company logo

Note: Calix believes the information in this publication to be accurate as of publication date, and is not responsible for error. Product Specifications are subject to change without notice.